

# (13) SCHEDULE

(14) to EC-Type Examination Certificate KEMA 01ATEX2124 X Issue No. 3

#### (15) **Description**

Self-limiting heating element Cameo-S, models CT-\*A, LP-\*A, LP-\*S, CS-\*S, SP-\*A, LP-0AHP and LP-0SHP and Smart Heater, models SM-\*A, SM-0AHP, SMLP-\*A and SMLP-0AHP for fixed installation, made of aluminium or stainless steel, provided with PTC-heating elements.

The relation between the Model and the Temperature class/ code is given in the following table:

Model	Temperature class/ code
xx-0x / xx-1x	T3 / T200 °C
xx-2x / xx-3x / xx-4x	T4 / T135 °C

#### Electrical data

Rated voltage	12-36 V or 110-240 V
Power	Max. 500 W

### Routine tests

Routine tests according to Clause 16 of EN 60079-1 are not required since the free internal volume is less than  $10~\text{cm}^3$ .

#### (16) Test Report

KEMA No. 212100300.

## (17) Special conditions for safe use

Ambient temperature range -60 °C to +90 °C.

## (18) Essential Health and Safety Requirements

Assured by compliance with the standards listed at (9).

## (19) Test documentation

As listed in Test Report No. 212100300.

MEAN-P-Ex30 v2.1.2 Page 2/2