



Condor Technology Ltd.

DATASHEET: ELECTRICAL THERMOSTAT FIX THERM96 TH-*/* or THS-*/*



1 Application

The FixTherm96-Thermostats are often used as maximum thermostat in instrumentation cabinets with space-heating, to protect the equipment from overheating.

- Prevention of overheating
- Temperature protection

2 Features and Advantages

- Set-points up to 135°C
- Accurate set-point ($\pm 3^\circ\text{C}$)
- Small hysteresis
- Anodized Aluminium housing (Stainless steel housing available)
- Armoured electrical cable standard
- Suitable for T6 and T4 classification
- Can be used for 6A / 240 VAC/DC

3 Description

The housing is made from anodized Aluminium or on request Stainless Steel type 316.

When required in applications, e.g. analyzers, it is normal practice to use our Space-heaters and Direct-heaters in combination with these Fix-Therm96 thermostats (range from 10°C up to 135°C). The FixTherm96 can also be used for cooling purposes e.g. FixTherm TH-10/5F.

4 Range

Aluminium: TH-10/5 – going up with 5°C set-points e.g. 10/5 – 15/10 – 20/15 etc. up to 135°C maximum.

Stainless Steel bodies: identical range.



5 Technical data

Housing	:	Anodized Aluminium or Stainless Steel
Current / voltage	:	6A / 240 VAC
Cable	:	3x 0,75 sqmm
Material cable	:	silicone braided cable, optional: non-braided cable
Standard length	:	ca. 1 mtr
Other lengths	:	on request
Overall dimensions	:	o.d. 30 mm x 49 mm length
Weight	:	ca. 160 g.
Switch	:	SPST
Set-point tolerance	:	+/- 3°C
Hysteresis	:	ca. 2°C
Mounting bracket	:	available (B)
Ambient temp. range	:	-50 °C ... + 90 °C
EX protection class	:	II2 G Ex d IIC T6 or T4 : II2 D Ex tD A21 IP66 T85°C or T 135°C
Certification	:	KEMA 01ATEX2125X and IECEx DEK 11.0017



Condor Technology Ltd.



Copyright © Condor Technology Ltd. all rights reserved.



The information contained herein is believed to be reliable. Condor Technology Ltd. assumes no responsibility or liability whatsoever for any of the information contained herein.